

ASME BPVC.II.D.M-2025

SECTION II
MATERIALS

2025

ASME Boiler and
Pressure Vessel Code
An International Code

Part D
Properties (Metric)


ASME
SETTING THE STANDARD

Markings such as “ASME,” “ASME Standard,” or any other marking including “ASME,” ASME logos, or the ASME Single Certification Mark shall not be used on any item that is not constructed in accordance with all of the applicable requirements of the Code or Standard. Use of the ASME Single Certification Mark requires formal ASME certification; if no certification program is available, such ASME markings may not be used. (For Certification and Accreditation Programs, see <https://www.asme.org/certification-accreditation>.)

Items produced by parties not formally possessing an ASME Certificate may not be described, either explicitly or implicitly, as ASME certified or approved in any code forms or other document.

AN INTERNATIONAL CODE

2025 ASME Boiler & Pressure Vessel Code

2025 Edition

July 1, 2025

II MATERIALS

Part D

Properties (Metric)

ASME Boiler and Pressure Vessel Committee
on Materials



The American Society of
Mechanical Engineers

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: July 1, 2025

This international code or standard was developed under procedures accredited as meeting the criteria for American National Standards and it is an American National Standard. The standards committee that approved the code or standard was balanced to ensure that individuals from competent and concerned interests had an opportunity to participate. The proposed code or standard was made available for public review and comment, which provided an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity. ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor does ASME assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representatives or persons affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

The endnotes and preamble in this document (if any) are part of this American National Standard.



ASME Collective Membership Mark



ASME Single Certification Mark

All rights reserved. “ASME” and the above ASME symbols are registered trademarks of The American Society of Mechanical Engineers. No part of this document may be copied, modified, distributed, published, displayed, or otherwise reproduced in any form or by any means, electronic, digital, or mechanical, now known or hereafter invented, without the express written permission of ASME. No works derived from this document or any content therein may be created without the express written permission of ASME. Using this document or any content therein to train, create, or improve any artificial intelligence and/or machine learning platform, system, application, model, or algorithm is strictly prohibited.

Library of Congress Catalog Card Number: 56-3934

Adopted by the Council of The American Society of Mechanical Engineers, 1914; latest edition 2025.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2025 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

TABLE OF CONTENTS

List of Sections		xiii
Foreword		xiv
Statement of Policy on the Use of the ASME Single Certification Mark and Code Authorization in Advertising		xvi
Statement of Policy on the Use of ASME Marking to Identify Manufactured Items		xvi
Personnel		xvii
Correspondence With the Committee		xl
Summary of Changes		xlvi
Cross-Referencing in the ASME BPVC		xlvi
Subpart 1	Stress Tables	1
	Statement of Policy on Information Provided in the Stress Tables	1
	Guideline on Locating Materials in Stress Tables, and in Tables of Mechanical and Physical Properties	3
Subpart 2	Physical Properties Tables	1155
	Introduction	1155
Subpart 3	Charts and Tables for Determining Shell Thickness of Components Under External Pressure	1196
Mandatory Appendix 1	Basis for Establishing Stress Values in Tables 1A and 1B	1326
1-100	Derivation of Allowable Stress Values	1326
Mandatory Appendix 2	Basis for Establishing Design Stress Intensity Values for Tables 2A, 2B, and 4, and Allowable Stress Values for Table 3	1328
2-100	Derivation of Stress Intensity Values	1328
Mandatory Appendix 3	Basis for Establishing External Pressure Charts	1331
3-100	General	1331
3-200	Basis of Charts in Subpart 3	1331
3-300	Use of Charts in Subpart 3	1331
3-400	Background and Development of Theory	1331
3-500	Design Basis	1331
3-600	Criteria for Allowable Stresses	1332
3-700	Procedure and Responsibility for Chart Development	1334
3-800	Alternate Procedure for Determining Allowable Compressive Stresses	1337
3-900	References	1337
Mandatory Appendix 5	Guidelines on the Approval of New Materials Under the ASME Boiler and Pressure Vessel Code	1338
5-100	Code Policy	1338
5-200	Application	1338
5-300	Chemical Composition	1340
5-400	Metallurgical Structure and Heat Treatment	1340
5-500	Mechanical Properties	1340
5-600	Definitions for Data Collection Purposes	1340
5-700	Required Sampling	1341
5-800	Time-Independent Properties	1341
5-900	Time-Dependent Properties	1341
5-1000	Low-Temperature Properties	1343
5-1100	Toughness Data	1343
5-1200	Stress-Strain Curves	1343

5-1300	Fatigue Data	1343
5-1400	Physical Properties	1344
5-1500	Data Requirements for Welds, Weldments, and Weldability	1344
5-1600	Long-Term Properties Stability	1346
5-1700	Requests for Additional Data	1346
5-1800	New Materials Checklist	1346
5-1900	Requirements for Recognized National or International Specifications	1346
5-2000	Publication of Recognized National or International Specifications	1347
5-2100	CEN Specifications	1347
Mandatory Appendix 6	Basis for Establishing Stress Values in Tables 6A, 6B, 6C, and 6D	1348
6-100	Derivation of Allowable Stress Values	1348
Mandatory Appendix 7	Guidelines on Multiple Marking of Materials	1350
7-100	Background	1350
7-200	Guidelines	1350
Mandatory Appendix 9	Standard Units for Use in Equations	1352
Mandatory Appendix 10	Basis for Establishing Maximum Allowable Stress Values for Tables 5A and 5B	1353
10-100	Derivation of Allowable Stress Values	1353
Nonmandatory Appendix A	Issues Associated With Materials Used in ASME Code Construction ...	1355
A-100	General	1355
A-200	Metallurgical Changes That Can Occur in Service	1356
A-300	Uniform Corrosion	1363
A-400	Localized Corrosion	1366
A-500	Metallurgically Influenced Corrosion	1367
A-600	Mechanically Assisted Corrosion	1368
A-700	Environmentally Induced Embrittlement and Cracking	1369
A-800	Mechanical Damage Mechanisms	1373
Nonmandatory Appendix B	Developing Nominal Composition Designations for ASME Code Materials	1375
B-100	Background	1375
B-200	General Guideline for All Materials	1375
B-300	Guidelines for Developing Nominal Composition Designations for Ferrous Materials	1376
B-400	Guidelines for Developing Nominal Composition Designations for Nonferrous Materials	1376
B-500	Summary	1377
Nonmandatory Appendix C	Guidance for the Use of U.S. Customary and SI Units in the ASME Boiler and Pressure Vessel Code	1378
C-100	Use of Units in Equations	1378
C-200	Guidelines Used to Develop SI Equivalents	1378
C-300	Soft Conversion Factors	1380
Nonmandatory Appendix D	Guidelines for Rounding Minimum Specified Tensile and Yield Strength Values and for Establishing Anchor Points for Tensile and Yield Strength Trend Curves in Tables 1A, 1B, 2A, 2B, 3, 4, 5A, 5B, U, and Y-1	1381
D-100	Minimum Tensile Strength and Minimum Yield Strength Columns	1381
D-200	Selecting Anchor Point for Tensile and Yield Strength Trend Curves for All Situations in Which the Minimum RT Specified Values in One Unit System Are Not Precise Conversions of the Units in the Other System	1381
D-300	Significant Figures in the Allowable Stress, Tensile Strength, and Yield Strength Tables in Section II, Part D and in Code Cases	1382

Nonmandatory Appendix E	Material Data for Stress Analysis in the Time-Dependent Regime	1383
E-100	Introduction	1383

FIGURES

G	Geometric Chart for Components Under External or Compressive Loadings (for All Materials)	1197
CS-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Carbon or Low Alloy Steels With Specified Minimum Yield Strength Less Than 207 MPa .	1199
CS-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Carbon or Low Alloy Steels With Specified Minimum Yield Strength 207 MPa and Higher	1200
CS-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Carbon Steel and Low Alloy Steels With Specified Minimum Yield Strength 260 MPa and Higher for Temperatures 150°C and Less	1201
CS-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for SA-537 Thickness 64 mm and Less	1202
CS-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for SA-508 Class 1, Grades 2 and 3; SA-508 Class 2, Grade 2; SA-533 Class 1, Grades A, B, C, and D; SA-533 Class 2, Grades A, B, C, and D; or SA-541 Grades 2 and 3	1203
CS-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Carbon Steel With Specified Minimum Yield Strength of 138 MPa	1204
HT-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Quenched and Tempered Low Alloy Steel With Specified Minimum Yield Strength of 689 MPa and Thickness 64 mm and Less	1205
HT-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for SA-508 Grade 4N, Class 2 or SA-543 Types B and C, Class 2 With Specified Minimum Yield Strength of 689 MPa	1206
HA-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 18Cr–8Ni, Type 304	1207
HA-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 16Cr–12Ni–2Mo, Type 316	1208
HA-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 18Cr–8Ni–0.035 Maximum Carbon, Type 304L	1209
HA-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 18Cr–8Ni–Mo–0.035 Maximum Carbon, Type 316L	1210
HA-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic–Ferritic Steel 18Cr–5Ni–3Mo S31500 and Austenitic–Ferritic Steel 25Cr–6Ni–Mo–N S32053	1211
HA-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 21Cr–11Ni–N S30815	1212
HA-7	Chart for Determining Shell Thickness of Components Under External Pressure Developed for SA-564 Type 630 H1150 (17Cr–4Ni–4Cu S17400)	1213
HA-8	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic–Ferritic Steel 25Cr–7Ni–3Mo–2W–0.28N S39274	1214
HA-9	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Steel 25Cr–7.5Ni–3.5Mo–N–Cu–W S32760	1215
HA-10	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Austenitic Stainless Steel 24Cr–17Ni–6Mn–4.5Mo–N S34565	1216
CI-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Cast Iron	1217
CD-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Cast Ductile Iron With a Specified Minimum Yield Strength of 275 MPa	1218
CD-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Cast Ductile Iron With a Specified Minimum Yield Strength of 200 MPa	1219
NFA-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 3003 in O Temper	1220
NFA-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 3003 in H14 Temper	1221

NFA-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 3004 in O Temper	1222
NFA-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 3004 in H34 Temper	1223
NFA-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5154 in O Temper	1224
NFA-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5454 in O Temper	1225
NFA-7	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 1060 in O Temper	1226
NFA-8	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5052 in O Temper	1227
NFA-9	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5086 in O Temper	1228
NFA-10	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5456 in O Temper	1229
NFA-11	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Alloy 5083 in O Temper	1230
NFA-12	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Welded Aluminum Alloy 6061-T6	1231
NFA-13	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Welded Aluminum Alloy 6061-T4	1232
NFC-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Copper, Type DHP	1233
NFC-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Copper-Silicon Alloy C65500	1234
NFC-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed 90-10 Copper-Nickel Alloy	1235
NFC-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed 70-30 Copper-Nickel Alloy	1236
NFC-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Welded Copper-Iron Alloy Tube C19400 (SB-543 Welded)	1237
NFC-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for SB-75 and SB-111 Light Drawn Seamless Copper Tubes, Alloys C10200, C12000, C12200, and C14200	1238
NFC-7	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Copper, SB-75, UNS C12200, Temper O50	1239
NFC-8	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Aluminum Bronze Alloy C61400	1240
NFN-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Low Carbon Nickel N02201	1241
NFN-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel N02200	1242
NFN-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel-Copper Alloy N04400	1243
NFN-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel-Chromium-Iron Alloy N06600	1244
NFN-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum Alloy N10001	1245
NFN-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum-Chromium-Iron Alloy N10003	1246
NFN-7	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Iron-Chromium-Molybdenum-Copper Alloy N08825	1247
NFN-8	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel-Iron-Chromium Alloy N08800	1248

NFN-9	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel-Iron-Chromium Alloy N08810	1249
NFN-10	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Low Carbon Nickel-Molybdenum-Chromium Alloy N10276	1250
NFN-11	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Solution Treated Nickel-Chromium-Iron-Molybdenum-Copper Alloy N06007	1251
NFN-12	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Chromium-Nickel-Iron-Molybdenum-Copper-Columbium Alloy N08020	1252
NFN-13	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Iron-Chromium-Silicon Alloy N08330	1253
NFN-14	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Chromium-Molybdenum Alloy N06455	1254
NFN-15	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum Alloy N06002	1255
NFN-16	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum Alloy N10665	1256
NFN-17	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Annealed Nickel-Chromium-Molybdenum-Columbium Alloy N06625 (SB-443, SB-444, and SB-446)	1257
NFN-18	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum-Chromium-Iron-Copper Alloy N06985 Having a Minimum Yield Strength of 240 MPa	1258
NFN-19	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Molybdenum-Chromium-Iron-Copper Alloy N06985 Having a Minimum Yield Strength of 207 MPa	1259
NFN-20	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Work-Hardened Nickel	1260
NFN-21	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel-Chromium-Iron Alloy N06600 (Specified Minimum Yield Strength 276 MPa)	1261
NFN-22	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Solution Annealed Ni-Cr-Mo-Cb Alloy, Grade 2 N06625	1262
NFN-23	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Cold Worked Nickel-Iron-Chromium Alloy N08800	1263
NFN-24	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Nickel Alloy N06230	1264
NFN-25	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Stress Relieved Nickel Alloy N02200	1265
NFN-26	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Alloy S31277	1266
NFN-27	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Alloy N06035	1267
NFT-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Unalloyed Titanium Grade 3 (UNS R50550)	1268
NFT-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Unalloyed Titanium Grade 2 (UNS R50400)	1269
NFT-3	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Titanium Grade 1 (UNS R50250)	1270
NFT-4	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Titanium Grade 9 Alloy (UNS R56320)	1271
NFT-5	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Titanium Grade 12 Alloy (UNS R53400)	1272
NFT-6	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Titanium Grade 38 (UNS R54250)	1273
NFZ-1	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Zirconium Alloy (UNS R60702)	1274

NFZ-2	Chart for Determining Shell Thickness of Components Under External Pressure Developed for Zirconium Alloy (UNS R60705)	1275
3-500.1	Temperature Limits for Application of Section II External Pressure Charts for Cylinder Under External Pressure	1333
3-500.2	Temperature Limits for Application of Section II External Pressure Charts for Cylinder Under Axial Compression	1334
3-500.3	Temperature Limits for Application of Section II External Pressure Charts for Sphere Under External Pressure	1335
3-700.1	Normalization of Test σ - ϵ to σ_{ymin} and E_{code}	1336
E-100.2-1	Permissible Time/Temperature Conditions for Material That Has Been Cold Worked >5% and <20% and Subjected to Short-Time High Temperature Transients	1385
E-100.4-1	S_{mt} — Allowable Stress Intensity Values, MPa, Type 304 SS — 207-YS, 518-UTS (207-YS, 483-UTS)	1388
E-100.4-2	S_{mt} — Allowable Stress Intensity Values, MPa, Type 316 SS — 207-YS, 518-UTS (207-YS, 483-UTS)	1389
E-100.4-3	S_{mt} — Allowable Stress Intensity Values, MPa, Ni-Fe-Cr (Alloy 800H)	1390
E-100.4-4	S_{mt} — Allowable Stress Intensity Values, MPa, 2 $\frac{1}{4}$ Cr-1Mo	1392
E-100.4-5	S_{mt} — Allowable Stress Intensity Values, MPa, 9Cr-1Mo-V	1393
E-100.5-1	S_t — Allowable Stress Intensity Values, MPa, Type 304 SS	1394
E-100.5-2	S_t — Allowable Stress Intensity Values, MPa, Type 316 SS	1395
E-100.5-3	S_t — Allowable Stress Intensity Values, MPa, Ni-Fe-Cr (Alloy 800H)	1396
E-100.5-4	S_t — Allowable Stress Intensity Values, MPa, 2 $\frac{1}{4}$ Cr-1Mo	1397
E-100.5-5	S_t — Allowable Stress Intensity Values, MPa, 9Cr-1Mo-V	1398
E-100.7-1	Expected Minimum Stress-to-Rupture Values, MPa, Type 304 SS	1400
E-100.7-2	Expected Minimum Stress-to-Rupture Values, MPa, Type 316 SS	1401
E-100.7-3	Expected Minimum Stress-to-Rupture Values, MPa, Ni-Fe-Cr (Alloy 800H)	1402
E-100.7-4	Expected Minimum Stress-to-Rupture Values, MPa, 2 $\frac{1}{4}$ Cr-1Mo	1403
E-100.7-5	Expected Minimum Stress-to-Rupture Values, MPa, Ni-Cr-Fe-Mo-Cb (Alloy 718)	1404
E-100.7-6	Expected Minimum Stress-to-Rupture Values, MPa, 9Cr-1Mo-V	1405
E-100.15-1	S_{mt} — Allowable Stress Intensity, Type 304 SS, Bolting	1410
E-100.15-2	S_{mt} — Allowable Stress Intensity, Type 316 SS, Bolting	1411
E-100.15-3	S_{mt} — Allowable Stress Values, MPa, Alloy 718, Bolting	1412
E-100.16-1	Design Fatigue Strain Range, ϵ_t , for 304 SS	1413
E-100.16-2	Design Fatigue Strain Range, ϵ_t , for 316 SS	1414
E-100.16-3	Design Fatigue Strain Range, ϵ_t , for Ni-Fe-Cr Alloy 800H	1415
E-100.16-4	Design Fatigue Strain Range, ϵ_t , for 2 $\frac{1}{4}$ Cr-1Mo Steel	1416
E-100.16-5	Design Fatigue Strain Range, ϵ_t , for 9Cr-1Mo-V Steel	1417
E-100.17-1	Time-Temperature Limits for Application of Section II External Pressure Charts for Cylinder Under Axial Compression	1418
E-100.17-2	Time-Temperature Limits for Application of Section II External Pressure Charts for Sphere Under External Pressure	1419
E-100.17-3	Temperature Limits for Application of Section II External Pressure Charts for Cylinder Under External Pressure	1420
E-100.18-1	Average Isochronous Stress-Strain Curves for Type 304 SS at 427°C	1421
E-100.18-2	Average Isochronous Stress-Strain Curves for Type 304 SS at 454°C	1422
E-100.18-3	Average Isochronous Stress-Strain Curves for Type 304 SS at 482°C	1423
E-100.18-4	Average Isochronous Stress-Strain Curves for Type 304 SS at 510°C	1424
E-100.18-5	Average Isochronous Stress-Strain Curves for Type 304 SS at 538°C	1425
E-100.18-6	Average Isochronous Stress-Strain Curves for Type 304 SS at 566°C	1426
E-100.18-7	Average Isochronous Stress-Strain Curves for Type 304 SS at 593°C	1427
E-100.18-8	Average Isochronous Stress-Strain Curves for Type 304 SS at 621°C	1428
E-100.18-9	Average Isochronous Stress-Strain Curves for Type 304 SS at 649°C	1429
E-100.18-10	Average Isochronous Stress-Strain Curves for Type 304 SS at 677°C	1430
E-100.18-11	Average Isochronous Stress-Strain Curves for Type 304 SS at 704°C	1431
E-100.18-12	Average Isochronous Stress-Strain Curves for Type 304 SS at 732°C	1432
E-100.18-13	Average Isochronous Stress-Strain Curves for Type 304 SS at 760°C	1433